

Beauty Acrylic Distemper

PRODUCT DESCRIPTION

Nerolac Acrylic Distemper is supplied in paste form, and it can be used for the decoration of fully matured plasterwork, concrete, brickwork and asbestos surfaces. The paste is bound with a stable acrylic medium.

PERFORMANCE FEATURES & BENEFITS

- Economical Distemper
- Ease of application
- Good washability
- Eye soothing matt finish..

RECOMMENDED USAGE

Nerolac Acrylic Distemper is recommended for interior use only. It can be applied on ceilings and wall surfaces where a matt finish, free from irritating glares due to light reflection is desired.

SURFACE PREPARATION

Ensure the surface is clean, dry free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down using suitable abrasive paper and thereafter wipe off. Treat fungus affected area using Nerolac Fungicidal Solution. Allow to react for 6 – 8 hrs. Apply a coat of suitable Primer* followed by Nerolac Wall Putty to level the dents and make the surface uniform. Apply again a coat of suitable Primer*. Then apply two to three coats of Nerolac Acrylic Distemper. Apply 2nd coat of Melamine crystal clear Top Coat. Allow it to dry for 6-8 hrs.

Coated surfaces must be allowed to dry completely before use. Application pictorial is as follows

RECOMMENDED SYSTEM FOR APPLICATION

Sand the Surface with Emery Paper and Wipe clean before application of subsequent coat

* Nerolac Cement Primer (Water Thinnable/Solvent Thinnable) or Goody Universal Primer (Solvent Thinnable) or Goody Water Thinnable Cement Primer

Minimum 8 Hrs for Solvent Thinnable Primer & Minimum 4-6 Hrs for Water Thinnable Primer:

TECHNICAL DATA

Coverage**	On Smooth and non-absorbent surface.150 - 170 sq. ft/Kg/coat.
Drying Time	Surface Dry: 30 minutes.
@27° ± 2°C & RH 60 ± 5%	Recoating: After 3 - 4 hours
Gloss Levels/ Sheen levels	Matt.
Thinning	Add 1 Lit of Water in 1.5 Kg of Distemper.
Flash Point	NA.
Stability of Thinned Paint	Use within 24 hrs.
Shelf-Life:	1 year from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

**Actual coverage may vary depending on methode & condition of application, surface roughness.

PRECAUTIONS

- Refer MSDS for "Nerolac Acrylic Distemper" for safety measures & Precautions.
- Store in well ambient conditions, Ventilated locations & away from the source of ignition and fire.
- Keep away from children.
- In case of eye/skin contact wash with plenty of water.
- Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
- Do not apply when ambient temperature might drop to level below 10°C within 4 hrs of application.
- New plaster should be allowed to cure for minimum 12 weeks.
- Avoid extra thinning for better results.
- Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir well tinted paint after tinting & before application.
- The container must be tightly closed when not in use. Stir well and strain before use.
- Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask

PACK SIZES

1 kg, 2 kg, 5 kg, 10 kg & 20 kg.

SHADE RANGE

As per colourscapes fandeck & shade card.

