

EXTERIOR ACRYLIC WALL PRIMER



**SHALIMAR
PAINTS**

Shalimar Exterior Acrylic Wall Primer is a water dilutable exterior primer based on specially designed acrylic emulsion suitable for exterior walls. It acts as a sealer coat to prevent the undesirable absorption of finishing paint by the surface and thereby enhancing coverage of finishing paint.

Areas of Application	Exterior surfaces of sand plaster concrete, brick, asbestos, etc.
Finish	Smooth & Matt
Viscosity	9-12 poise / 30°C
Surface Dry	Within 20 minutes
Interval Between Coats	4 Hours
No. of Coats	Single coat is generally recommended. But for highly absorbing surface two coats to be applied to ensure proper sealing.
Average Covering	120 – 140 sq. ft./Lt/coat by brush application (depending of porosity of the wall)
Thinner Recommended	Potable water
Thinning Ratio	60% by volume
Flash Point (abel closed)	Not applicable
Surface Preparation	Ensure the surface is dry and free from algae, fungi, dust, dirt, grease, oil & loose matters.

Actual technical details may vary due to factors such as method & condition of application & type of surface.



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India)

P: +91-124-4616600 | **F:** +91-124-4616659

E: askus@shalimarpaints.com | www.shalimarpaints.com

