

# DISTEMPER

## GOODY SYNTHETIC DISTEMPER

### PRODUCT DESCRIPTION

Goody Synthetic Distemper is a product specially developed in the economy range for customers residing in rural and semi-urban areas. It gives a pleasant smooth finish on walls at an economic price, and offers a favourable substitute for the lime wash (chuna) application, at a comparable price. The product is supplied in a paste form and can be applied on plasterwork, concrete, brickwork and asbestos surfaces for protection and decoration.

### PERFORMANCE FEATURES & BENEFITS

A very economical product.  
Smooth and pleasant matt finish.  
Ease of application.  
Priming of the substrate not required.

### RECOMMENDED USAGE

Goody synthetic distemper is recommended for interior use only. It can be applied on ceilings and wall surfaces where a smooth matt finish is desired with an economic advantage.

### SURFACE PREPARATION

Ensure the surface is clean, dry and free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using a suitable abrasive paper and thereafter wipe off. Treat the fungus affected area by using Nerolac Fungicidal Solution. Then apply two to three coats of Goody Synthetic Distemper.

### RECOMMENDED SYSTEM FOR APPLICATION

#### STEP 1

Finish  
(2 - 3 coats)  
Goody Synthetic  
Distemper

Dry 3 - 4 hrs.  
in between coats.





## TECHNICAL DATA

<b>COVERAGE**</b>	On a smooth, non-absorbent surface. 140 - 160 sq. ft. / kg. / coat.
<b>DRYING TIME</b>	Surface Dry : 30 mins.
<b>@27° ± 2°C &amp; RH 60 ± 5%</b>	Recoating : After 3 - 4 hrs.
<b>GLOSS LEVELS / SHEEN LEVELS</b>	Matt.
<b>THINNING</b>	Add 1 ltr. of water in 1.5 kg. of Distemper.
<b>FLASH POINT</b>	NA.
<b>STABILITY OF THINNED PAINT</b>	Use within 24 hrs.

\*\*Actual coverage may vary depending on Method, Condition of Application, Surface Porosity & Shade.

## PRECAUTIONS

- 1) Refer to MSDS for "Goody Synthetic Distemper" for safety measures & precautions.
- 2) Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
- 3) Keep away from children.
- 4) In case of eye / skin contact, wash with plenty of water.
- 5) Inhalation / Injection will cause danger. In either case, move to fresh air & consult a medical practitioner.
- 6) Do not apply when ambient temperature might drop below 10°C within 4 hrs. of application.
- 7) The new plaster should be allowed to cure for minimum 12 weeks.
- 8) Avoid extra thinning for better results.
- 9) Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. After tinting & before application, stir the tinted paint well.
- 10) The container must be tightly closed when not in use. Stir well and strain before use.
- 11) Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face masks.

## POST APPLICATION INSTRUCTIONS

NA.

## SAFETY FEATURES

Non-flammable.

## PACK SIZES

1 kg. pouch.

## SHADE RANGE

Supplied as Ujala (White) and other attractive shades, as shown in the Std. Shade Card.