



PRIMER-INTERIOR

GOODY UNIVERSAL PRIMER WHITE (SOLVENT THINNABLE)

PRODUCT DESCRIPTION

Goody Universal Primer White is formulated by using a synthetic resin medium and a suitable combination of pigments and extenders, to ensure deep penetration and sealing of porous surfaces. It is suitable for interior application, for priming of plastered surfaces and other masonry works. It makes the surface less absorbent.

PERFORMANCE FEATURES & BENEFITS

- Good adhesion to substrate.
- Very good intercoat adhesion.
- Seals dry porous surfaces.
- Good hardness.
- Ease of application.

RECOMMENDED USAGE

Goody Universal Primer can be applied on plastered surfaces, asbestos sheets, concrete, brick works, wood etc. prior to over coating with solvent based or water based paints.

SURFACE PREPARATION

Ensure the surface is clean, dry and free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using a suitable abrasive paper and thereafter wipe off. Treat the fungus affected area by using Nerolac Fungicidal Solution. Allow it to react for 6 – 8 hrs. Apply a coat of Goody Universal Primer White before application of the required top coats.

RECOMMENDED SYSTEM FOR APPLICATION

STEP 1		STEP 2		STEP 3		STEP 4
GUP* White (1coat)	Dry Min. 8 hrs.	Putty Nerolac Wall Putty	Dry 6 - 8 hrs.	GUP* White (1coat)	Dry Min. 8 hrs.	Subsequent finishing coats.#

Sand the surface with Emery Paper and wipe clean before application of subsequent coats.

*Goody Universal Primer.

#Pl. look for the individual finishing system given in respective Product Data Sheet.





TECHNICAL DATA

COVERAGE**	On a smooth, non-absorbent surface. 150 – 170 sq. ft. / ltr. / coat.
DRYING TIME	Surface Dry : Max. 1 hr.
@27° ± 2°C & RH 60 ± 5%	Recoating : Min. 8 hrs.
GLOSS LEVELS / SHEEN LEVELS	Matt.
THINNING	Upto 30% by volume using Nerolac General Purpose Thinner.
FLASH POINT	Not below 30°C.
STABILITY OF THINNED PAINT	Use within 24 hrs.

***Actual coverage may vary depending on Method & Condition of Application, Surface Roughness & Surface Porosity.*

PRECAUTIONS

- 1) Refer to MSDS for "Goody Universal Primer White" for safety measures & precautions.
- 2) Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
- 3) Keep away from children.
- 4) In case of eye / skin contact, wash with plenty of water.
- 5) Inhalation / Injection will cause danger. In either case, move to fresh air & consult a medical practitioner.
- 6) Do not apply when ambient temperature might drop to level below 10°C within 4 hrs. of application.
- 7) The new plaster should be allowed to cure for minimum 12 weeks.
- 8) Avoid extra thinning for better results.
- 9) Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well after tinting & before application.
- 10) The container must be tightly closed when not in use. Stir well & strain before use.
- 11) Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face masks.

POST APPLICATION INSTRUCTIONS

Apply a finishing coat within 7 – 8 days of primer application.

SAFETY FEATURES

Flammable.

PACK SIZES

1 ltr., 4 ltrs., 10 ltrs. & 20 ltrs.

SHADE RANGE

White.