

Goody Universal Primer

PRODUCT DESCRIPTION

Goody Water Thinnable Cement Primer is an economical water thinnable primer, specially formulated by dispersion of White pigments and extenders in a copolymer Emulsion Medium. It is suitable for Interior application for priming of plastered surfaces and other masonry works. It makes the surface less absorbent..

PERFORMANCE FEATURES & BENEFITS

- Good adhesion to substrate
- Very good intercoat adhesion
- Good hardness
- Ease of application.

RECOMMENDED USAGE

Goody Universal Primer can be applied on plastered surfaces, asbestos sheets, concrete, brick works, wood etc. prior to over coating with solvent based or water based paints.

SURFACE PREPARATION

Ensure the surface is clean, dry free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down using suitable abrasive paper and thereafter wipe off. Treat fungus affected area using Nerolac Fungicidal Solution. Allow to react for 6 – 8 hrs. Apply a coat of Goody Universal Primer White before application of required top coats.

RECOMMENDED SYSTEM FOR APPLICATION

* Goody Universal Primer

Pl. look for the individual finishing system given in respective Product Data Sheet.

TECHNICAL DATA

Coverage**	On Smooth and non-absorbent surface.150 - 170 sq. ft/Kg/coat.	
Drying Time	Surface Dry: Max 1 hr.	
@27° ± 2°C & RH 60 ± 5%	Recoating: Min. 8 hrs.	
Gloss Levels/ Sheen levels	Matt.	
Thinning	Upto 30% by volume using Nerolac General Purpose Thinner	
Flash Point	Not below 30°C	
Stability of Thinned Paint	Use within 24 hrs.	
Shelf-Life:	1 year from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.	

**Actual coverage may vary depending on method & condition of application, surface roughness & surface porosity

PRECAUTIONS

- Refer to the MSDS for "Goody Universal Primer White" for safety measures & precautions.
- Store in well ambient conditions, Ventilated locations & away from the source of ignition and fire.
- Keep away from children.
- In case of eye/skin contact wash with plenty of water.
- Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
- Do not apply when ambient temperature might drop to level below 10°C within 4 hrs of application.
- New plaster should be allowed to cure for minimum 12 weeks.
- Avoid extra thinning for better results.
- Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir well tinted paint after tinting & before application.
- The container must be tightly closed when not in use. Stir well and strain before use.
- Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

PACK SIZES

1 ltr, 4 ltrs., 10 ltrs. & 20 ltrs.

SHADE RANGE

White.

