

# ShaliPlast SP



High Range Water Reducing Cum Retarding Admixture

STP Limited

## Description

**ShaliPlast SP** (formerly known as ShaliCon 537) is a high range water-reducing admixture formulated specifically to extend the working time of concrete. It is based on Naphthalene Formaldehyde.

**ShaliPlast SP** conforms to specification prescribed in IS 9103 & ASTM C 494, Type G

## Characteristics

Colour	Amber brown	Specific Gravity	1.20 ± 0.03
pH	7 – 8	Chloride Content	Nil

## Application

- High performance concrete.
- Ready mix concrete.
- Flowing concrete.
- Heavily reinforced concrete.
- Pumpable concrete.
- Concrete for precast slabs.

## Advantages

- Produces Flowing concrete with controlled delay of slumps loss and workability.
- Reduces cracking and permeability of hardened concrete.
- Reduces segregation and bleeding in the plastic concrete.
- Significantly reduces concrete placement time and cost.
- Long time workability retention.
- Enable transport of concrete to distant places

## Application Methodology

- Add **ShaliPlast SP** to the dosing water. It should not come into contact with dry cement.
- Charge all concrete material in the proper order into the mixer with about 70 % of the mixing water and mix for the three minutes. Add rest quantity of water with admixture to obtain the required slump and mix for three addition minutes.
- Forms for walls or narrow sections must be watertight, strong and must have good bracing.
- During the “Flowing period” the concrete will exert a higher pressure at the base of the form than conventional concrete. Form work for slabs is the same as for conventional concrete.
- Compatible with all types of Portland cement including SRC (Sulphate Resistance Cement) and not compatible with high alumina cement.

## Dosage

0.5 – 2 % by weight of cement. Do not allow over dosing. Due to overdose bleeding or increase in setting time will happen. It is advisable to carry out a trial to establish the exact & optimal dosage rate depending upon set retardation required.

## Health & Safety

- **ShaliPlast SP** is non-toxic.
- Any splashes on the skin should be washed immediately with water.
- Splashes on the eyes should be washed immediately with water and seek medical advice.

### Packing

Available in 20 kg & 200 kg drum.

### Storage

Store in a cool dry place. under shed. away from heat.

### Shelf Life

9 months in original sealed condition.



**STP Limited**  
**Advisory Cell**  
**+91 81302 81114**  
Waterproofers to the Nation

### STP's Businesses

Waterproofing & Insulation  
Road Surfacing  
Pipeline Coating  
Repairs & Rehabilitation  
GARA (Grouts & Admixtures)  
Other Powder Products  
Sealant & Additives  
Epoxy Flooring  
Protective / Anti-Corrosive Coating  
Other Products



Call us : +91 98220 27368  
Nilkamal Paints & Hardware