ShaliPrime[®] PUM





Description

ShaliPrime[®] PUM is a Single component polyurethane based primer.

Characteristics

Pot Life @30 ^o C, hrs	5 - 6	DFT in microns		< 50 microns	
Surface dry ,@ 30 ^o C, RH 55%	25 - 35 minute	Recoating time, hrs		24 Max	. 0
Aspect	Light brown, clear	Theoretical	Coverage	8 -1 0	
	liquid	m2 / L *	O		
* Depending upon surface condition.	·				
 • Concrete / metal surfaces. 			30	, dub	
dvantages					
 Better adhesion and flexibility. Chemical resistance. Highly penetrative in concrete statements 	surface.	0	Y.		

Application

Advantages

- Better adhesion and flexibility.
- Chemical resistance.
- Highly penetrative in concrete surface.

Application Methodology

- Ensure that surface is cleaned from oil free compressed air, sandblasting, wire brushes or • other mechanical means to ensure removal of all rust, oil, grease, dirt, or any other loose particle prior to application of primer.
- Ensure that the surface is moisture free before application.
- Apply ShaliPrime[®] PUM on cleaned and dried surface by brush or airless spray.

Health & Safety

- Do not allow ShaliPrime[®] PUM to come in contact with the skin and eyes, or be swallowed. •
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and • water. Do not use solvent to clean the contacted area.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
 - If swallowed seek medical attention immediately do not induce vomiting. In case of fire use dry chemical or carbon dioxide extinguishers.

Packing

Available in 20 L container.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP's Businesses Waterproofing & Insulation **Road Surfacing Pipeline Coating** collus : rol points & Hordware **Repairs & Rehabilitation GARA (Grouts & Admixtures)**



Visit us at : www.stpltd.com or Email at : info@stpltd.com