# **ShaliTex Primer**



# STP Limited

ShaliTex Prime

#### **Description**

**ShaliTex Primer** is a solvent based bituminous primer that seals pores in surfaces such as concrete and improves the adhesion of bituminous materials that are to be applied to the substrate. It is suitable for brush or spray application. It conforms to the requirement of IS: 3384-1986.

# **Characteristics**

Consistency	Brushable &	Setting time at ambient	24
-	Sprayable	temperature, hr	
Theoretical Coverage, L/m <sup>2</sup> *	0.30	Service Temperature	5 – 50 <sup>0</sup> C
1		Water Content	0.20 %
Specific Gravity	0.90	Flash Point	40 °C Min
* Depending upon ourfood condition			×.

Depending upon surface condition.

#### **Application**

- Priming bituminous, concrete or masonry surfaces prior to laying membrane promotes bonding, whether self-adhesive or otherwise.
- Applied in canal lining joints and concrete floor joints prior to pouring of the bitumen sealing compound for bonding.

#### **Advantages**

- Seal pores on surfaces such as concrete.
- Improves the adhesion of bituminous material that is to be applied to the substrate.

# **Application Methodology**

- Ensure not to apply when temperature is less than 5 <sup>o</sup>C or during foggy period.
- Before applying the primer make the concrete surfaces free from dust and sand particles by brooming and allow it to dry. Concrete should be cured and should be eight days old.
- **ShaliTex Primer** should be thoroughly stirred before use and applied to the substrate by means of brush, roller or spray at the rate of 0.30 L/m<sup>2</sup>.
  - Allow it to dry for 24 hr.

# Health & Safety

- Lid of container should be firmly fixed, when not in use.
- ShaliTex Primer is inflammable and hence keep away from heat.
- Use goggles and hand glove during application.
- Clean hands with warm soap water after application.

# Packing

Available in 20 L & 200 L drum.

# Storage

Keep in cool and dry place, in air tight container, under shed, away from heat.



**STP's Businesses** Waterproofing & Insulation **Road Surfacing Pipeline Coating** collus : 491 points & Hardware **Repairs & Rehabilitation GARA (Grouts & Admixtures)** 



Visit us at : www.stpltd.com or Email at : info@stpltd.com