

Lustrol Aluminium Paint



**SHALIMAR
PAINTS**

A two pack general purpose Aluminium Paint having very good lustre & protective properties with heat resistance up to 250°Celsius. This is suitable for both internal and external uses in Buildings, Offices, Factories, Industrial Plants, Warehouses, etc. for application on storage tanks, machinery, bridges, railings, grills, gates, roofs, pipes, picture frames, etc. This is also suitable as a heat resistant coating for Chimney stacks, boiler fronts, duct work, piping and furnace structure.

Directions for use:

- The surface to be painted should be dry and free from oil, grease, dust, rust and loose matters. As heat resistant coating the paint to be applied directly on cleaned metal surface. For other uses (below 100°Celsius) the paint should go on appropriate primers (Red Oxide Metal Primer, Red Oxide Zinc Chromate Primer, Red Lead Primer or Zinc Chromate Primer Yellow).

Mixing	Al. Paste & medium supplied in proportionate quantities
Method of Application	Brushing / Spraying
Hard Drying Time	8 hours
Dry Film Thickness	10 – 12 micron / coat
Theoretical Spreading Rate	21 – 18 sq.m. / lt. / coat
Colour	Colour of Aluminium
Finish	Smooth with bright metallic effect
Heat Resisting Capacity (Intermittant Dry Heating)	250°C
Keeping Properties	Not less than one year
Shelf Life	Mixed paint should be used off within 48 hours
Flash Point (abel closed)	Over 30°C

Actual technical details may vary from the quote above due to factors such as method & condition of application, type of surface & surface preparation.



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India)

P: +91-124-4616600 | **F:** +91-124-4616659

E: askus@shalimarpaints.com | www.shalimarpaints.com

