



**SHALIMAR
PAINTS**

NO.1 PRIMER Acrylic Cement Primer

A water-based interior acrylic primer offering excellent sealing, priming and adhesion. Its excellent sealing and priming features ensures smooth & uniform finish to top coats.



**REDUCE
PATCHINESS**



GOOD COVERAGE



EXCELLENT SEALING



EXCELLENT ADHESION



EXCELLENT PRIMING



RECOMMENDED AREAS OF APPLICATION	Area of Use	Interior				
	Substrate	Concrete, Plaster, Masonry				
TECHNICAL DATA	Color Range	White				
	Finish	Matt				
	*Coverage	100-200 sq. ft/ltr <small>*Performance may vary due to factors such as method and condition of application, surface roughness and porosity.</small>				
	Ambient Temperature	Dry to Touch (RH-60)	Overcoating Interval			
			Minimum	Maximum		
			20°C	30 min	240 min	Overnight
			30°C	15 - 30 min	180 min - 240 min	Overnight
	40°C	15 min	180 min	Overnight		
Washability	Medium					
APPLICATION DATA	Recommended Tools	Brush/Roller				
	Thinning Recommended	Potable Water				
	Thinner ratio	80-100%				
SURFACE PREPARATION	<ul style="list-style-type: none">• New surface must be cured for 28 days before painting and free from all waterproofing issues.• Sand surface with 180 emery paper to remove dirt, dust, grease, loose flaking paint, algae, fungi etc. Wipe it clean.					



RECOMMENDED PRIMER	Apply a coat of No.1 Primer by thinning it with potable water 80-100% by volume. Allow it to dry for 6-8 hrs. Spot prime before and after filling nail holes, cracks, and other surface imperfections.	
PUTTY	Level the surface with Shalimar Magic Acrylic Wall Putty and allow it to dry for 4-6 hrs.	
RECOMMENDED PRIMER	Apply a coat of No.1 Primer by thinning it with potable water 80-100% by volume. Allow it to dry for 6-8 hrs.	
TOP COAT 1 COAT	Shalimar Interior Emulsions as recommended.	
TOP COAT 2 COATS	Shalimar Interior Emulsions as recommended.	
PACKAGING	Packs Available	1 ltr/4 ltrs/10 ltrs/20 ltrs
	Shelf life	3 years
SAFETY & PRECAUTIONS	<ul style="list-style-type: none"> • Stir well before thinning. Avoid extra thinning. • Wear suitable nose protection during sanding and surface preparation to avoid dust inhalation. Do not breathe vapors or spray. • In case of eye/skin contact, rinse with water and seek immediate medical attention. • Do not pour leftover paint down the drain. Ensure that there is adequate ventilation in the area where the product is being applied. • Container Lid must be closed tightly and stored in cool dry place. • Keep out of reach of children. 	



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India) | **P:** +91-124-4616600 | **F:** +91-124-4616659
E: askus@shalimarpaints.com | www.shalimarpaints.com