



**SHALIMAR
PAINTS**

SHAKTI EXTERIOR PRIMER

Exterior Acrylic Primer

A water-based exterior acrylic primer offering superior priming sealing and adhesion, ensuring better coverage and long-life to top coats.



**SUPERIOR
PRIMING**



**EXCELLENT
ADHESION**



**GOOD
COVERAGE**



**REDUCE
PATCHINESS**



RECOMMENDED AREAS OF APPLICATION	Area of Use	Exterior			
	Substrate	Concrete, Plaster, Masonry			
TECHNICAL DATA	Color Range	White			
	Finish	Matt			
	*Coverage	100-120 sq. ft/ltr <small>*Performance may vary due to factors such as method and condition of application, surface roughness and porosity.</small>			
	Ambient Temperature	Dry to Touch (RH-60)	Overcoating Interval		
			Minimum	Maximum	
		20°C	30 min	240 min	Overnight
		30°C	15 - 30 min	180 min - 240 min	Overnight
	40°C	15 min	180 min	Overnight	
Washability	Medium				
APPLICATION DATA	Recommended Tools	Brush/Roller			
	Thinning Recommended	Potable Water			
	Thinner ratio	40-50%			
SURFACE PREPARATION	<ul style="list-style-type: none">• New surface must be cured for 28 days before painting and free from all waterproofing issues.• Sand surface with 180 emery paper to remove dirt, dust, grease, loose flaking paint, algae, fungi etc. Wipe it clean.				



PUTTY (If required)**	A thin coat of Shalimar Shakti Wall Guard Putty to fill any dents/minor hair line cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.	
RECOMMENDED PRIMER	Apply a coat of Shalimar Shakti Exterior Acrylic Primer by thinning with potable water 40-50 % by volume. Allow it to dry for 4-6 hrs.	
TOP COAT 1 COAT	Shalimar Exterior Emulsions as recommended.	
TOP COAT 2 COATS	Shalimar Exterior Emulsions as recommended.	
PACKAGING	Packs Available	1 ltr/4 ltrs/10 ltrs/20 ltrs
	Shelf life	3 years
SAFETY & PRECAUTIONS	<ul style="list-style-type: none">• Stir well before thinning. Avoid extra thinning.• Wear suitable nose protection during sanding and surface preparation to avoid dust inhalation. Do not breathe vapors or spray.• In case of eye/skin contact, rinse with water and seek immediate medical attention.• Do not pour leftover paint down the drain. Ensure that there is adequate ventilation in the area where the product is being applied.• Container Lid must be closed tightly and stored in cool dry place.• Keep out of reach of children.	



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India) | **P:** +91-124-4616600 | **F:** +91-124-4616659
E: askus@shalimarpaints.com | www.shalimarpaints.com