

# SuperFlashStrip®

UV Resistant Self-Adhesive Flashing Bituminous Tape



STP Limited

## Description

**SuperFlashStrip®** is easy to apply, self-adhesive, pressure-sensitive, UV resistant waterproofing tape protected by aluminium-film and reinforced with polyester film. The adhesive bituminous compound is protected by silicon release film. **SuperFlashStrip®** gives lasting protection in all climates. **SuperFlashStrip®** bonds to a wide range of building materials to form an instant, permanent and water-tight seal. **SuperFlashStrip®** can be used in waterproofing and repair work.

## Characteristics

Colour	Silver	Elongation, %	
Thickness, mm	1.5	• Lengthwise	> 20
Impact Resistance, mm	1750	• Crosswise	> 20
Application Temperature	+5 °C / +45 °C	Service Temperature	-40 °C / +80 °C
Adhesion to		Tensile Strength	
• Primed Concrete	> 250 N	• Lengthwise	> 300 N / 50 mm
• Primed Steel	> 250 N	• Crosswise	> 300 N / 50 mm

## Application

- For sealing : frames and skylights, parapets, glass and plastic structure.
- For protecting : metal, plastic, asbestos cement, roofs and coverings in general.
- For repairing : tiles, gutters, metal pipes, metal plate or asbestos cement roofs.

## Advantages

- Easy to fix and compatible with most building material.
- No special tools required; only a sharp knife / scissors and a roller / cloth pad is enough.
- It does not require any torching and hence is suitable for use in all conditions.
- Cold applied, doesn't require heat or chemical bonding agents.
- Specially trained personnel are not required for application.
- Withstands climatic changes.
- Simple and quick application. Saves time and cost.

## Application Methodology

- Surface must be dry, compact, clean and free of loose particles and impurities; if the application surface area is porous, **SuperFlashStrip®** should be applied after a coat of ShaliPrime APP.
- Choose the most suitable width of **SuperFlashStrip®**.
- Unroll the tape until the desired length is reached.
- Remove the silicon released film and position the tape on the dry surface.
- Press with a roller or a cloth pad.
- In case of overlapping, the minimal overlapping width should be 10 mm.
- The best application temperature is above 5 °C.
- Do not apply when it is raining, freezing or snowing.

## Health & Safety

- Non hazardous for normal use.
- Use goggles and hand gloves during application.
- Clean hands with warm soap water after application.

## Packing

Rolls are individually shrink wrapped and placed in cartons. Standard length of each roll is 10 m, with width of 50 mm (2") / 100 mm (4") and thickness of 1.5 mm.

## Storage

Keep in cool dry place under the shed away from heat with atmospheric temperature ranging between +5 °C and +40 °C.



**STP Limited**  
**Advisory Cell**  
**+91 81302 81114**  
Waterproofers to the Nation

### STP's Businesses

Waterproofing & Insulation  
Road Surfacing  
Pipeline Coating  
Repairs & Rehabilitation  
GARA (Grouts & Admixtures)  
Other Powder Products  
Sealant & Additives  
Epoxy Flooring  
Protective / Anti-Corrosive Coating  
Other Products

80  
Years of  
Trust

Call us : +91 98250 27368  
Nilkamal Paints & Hardware