

WATER THINNABLE CEMENT PRIMER



**SHALIMAR
PAINTS**

Shalimar Water Thinnable Cement Primer is a specially designed acrylic emulsion based primer suitable for application of interior sand plastered surfaces, concrete, asbestos etc. It is quick drying, has fast recoating time and gives smooth finish too.

Direction of Use:

SURFACE PREPARATION

- Ensure the surface is free from rust, grease, oil & loose matter. Sand the surface with emery paper 180 and wipe clean.

METHOD OF APPLICATION

- After proper surface preparation, apply a first coat of primer depending on the surface of application. Allow drying for 6-8 hours. Smoothen the surface by filling dents with thin coat of putty and allow it to dry for 6-8 hours. Sand the surface with emery paper 180 and wipe clean. Apply another coat of primer and allow drying for 6-8 hours. Sand the surface with emery paper 320 and wipe clean.

Finish	Smooth & Matt
Coverage	120 – 140 sq. ft. per litre per coat by brush application
Supply Viscosity	10 +/- 1 poise/30°C
Surface Dry	20 minutes (at 30°C + / -1C & 65 + / -5% R.H)
Recoat Time	4 hours minimum
Thinner	Clean tap / potable water
Pack Size	500 ml / 1 litre / 4 litre
Shades Available	White
Areas of Application	Exterior / Interior surfaces of plaster, concrete, brickwork, asbestos etc.

Actual technical details may vary due to factors such as method & condition of application & type of surface.



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India)

P: +91-124-4616600 | F: +91-124-4616659

E: askus@shalimarpaints.com | www.shalimarpaints.com

