



**SHALIMAR  
PAINTS**

## XTRA PREMIUM ACRYLIC EMULSION

Shalimar Xtra is a premium exterior finish formulated with 100% pure acrylic emulsion. It's tough and durable film effectively withstand extreme tropical conditions of high rainfall, heat & cold, ensuring extra protection for exterior walls.



### Directions for use:

#### SURFACE PREPARATION

- New surface must be cured for 28 days before painting, free from all waterproofing issues.
- Surface must be free from dirt, dust, grease, loose flaking paint etc.
- Surface infected with algae/fungi needs to be removed thoroughly by vigorous wire brushing and water jetting or should be treated by 3% solution of bleaching powder & potable water. Allow it to react for 6-8 hours.

#### PUTTY (If required)

- Apply a thin coat of Shalimar Shakti Wall Guard Putty to fill any dents/minor hair line cracks or to smoothen the surface. Allow it to dry for 6-8 hours.

#### PRIMING

- Apply a coat of Shalimar (Exterior Primer/ Shakti Acrylic Primer) by thinning with potable water 40-50% by volume.
- Allow it to dry for 4-6 hours.

#### TOP COAT

- Apply 2-3 coats of Shalimar Xtra by thinning with potable water 40% by volume.
- Maintain a gap of 4-6 hours between coats.
- Avoid excess dilution for better performance.

**Application Surfaces:** All kinds of exterior plasters, concrete and masonry surfaces.

Apply an additional coat of Shalimar Xtra on horizontal surfaces or parapets for extra protection.




Finish	Smooth with Matt
Coverage	110 – 130 sq. ft. per litre per coat. (depends on substrate and application conditons)
Supply Viscosity	11+/- 3 poise at 30°C
Surface Dry	Within 25 minutes
Recoat Time	4 hours minimum
Thinner	Potable water
Primer	Apply a coat of Shalimar (Exterior Primer/ Shakti Acrylic Primer) by thinning with potable water 40-50% by volume.
Pack Size	1 litre / 4 litre / 10 litre / 20 litre
Area of Application	Exterior masonry, brick work, rendering & concrete

Actual technical details may vary due to factors such as method & condition of application & type of surface.



Call us: +91 98250 27268  
Nilkamal Paints & Hardware



THE ART & SCIENCE OF PAINTS

**Shalimar Paints Ltd.**

**Corp. Office:** 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India) | **P:** +91-124-4616600 | **F:** +91-124-4616659

**E:** askus@shalimarpaints.com | **www.shalimarpaints.com**

