

ALUMINIUM PAINT FOR GENERAL PURPOSE TO IS.2339/1963



**SHALIMAR
PAINTS**

A two pack general purpose Aluminium Paint for protective and decorative purposes, particularly where a heat-reflecting surface is required. The use of this material is extended to appliances connected with ammunitions.

Mixing	Al. Paste & medium supplied in proportionate quantities
Method of Application	Brushing / Spraying
Hard Drying Time	8 hours
Dry Film Thickness	12 - 14 micron / coat
Theoretical Spreading Rate	32 - 29 sq. m. / lt. / coat
Colour	Colour of Aluminium
Finish	Smooth with bright metallic effect
Heat Resisting Capacity (Intermittant Dry Heating)	250°C
Protection Against Corrosion (7 Days)	Passes: 2
Keeping Properties	Not less than one year
Shelf Life	Mixed paint should be used off within 48 hours.
Flash Point (label closed)	Over 30°C

Actual technical details may vary due to factors such as method & condition of application & type of surface.



THE ART & SCIENCE OF PAINTS

Shalimar Paints Ltd.

Corp. Office: 4th Floor, Plot No. 64, Sector-44, Gurgaon -122001, Haryana (India)

P: +91-124-4616600 | **F:** +91-124-4616659

E: askus@shalimarpaints.com | www.shalimarpaints.com

