



**BERGER**  **Protecton** PROTECTIVE COATINGS

**Torpedo High Gloss Synthetic Enamel**

**USES**

Recommended for use on exterior, structurals, pipelines, cladding, gantries, hand rails, cable trays etc

**SCOPE**

Torpedo Synthetic Enamel is designed to give a glossy durable topcoat for both interior and exterior exposure. It is ideally suitable for application on primed structures in polluted atmosphere with outstanding weather resistance and colour retention.

**PRODUCT DATA**

**Type :** Single Pack

**Composition :** Single component Alkyd Glossy enamel

**Application :** Brush, Roller, Conventional Spray

**Recommended DFT :** 30 – 40 microns per coat

**Theoretical Spreading Rate :** 10.5 – 14.0 m<sup>2</sup>./Ltr/coat

**Drying Time :**

TOUCH : 3 hours at 27±3°C

HARD : Overnight

**Overcoating Interval :**

MIN: : Overnight

**Flash Point :** Above 30° C

**Colour :** Assorted shades

**Packing :** 20 Ltrs.

**Thinner/Cleaner :** Thinner 800

**Finish:** Glossy

**Storage Life :** Upto twelve months as long as the

sealed containers are kept under cover in a dry place

under normal temperature conditions.

**RESISTANCE GUIDE**

**Chemical Resistance :**

EXPOSURES	SPLASH & SPILLAGE	MILD FUMES / OUTDOOR RESISTANCE
Acids	N/R	Fair
Alkalis	N/R	Fair
Solvents	N/R	Fair
Salt	Good	Good
Water	Good	Good

\* Not recommended for immersion.

**Temperature Resistance :**

Continuous : 80 ° C

Intermittent : 100 ° C

**Weatherability:** Good under mild industrial exposure

**Flexibility:** Excellent

**Abrasion Resistance:** Moderate

DATA SHEET No. : 009/ rev02

Issue Date : July 2003

**SURFACE PREPARATION**

**STEEL:** Remove grease, oil and other contaminants preferably by using Solvent as per SSPC SP1. Make full use of mechanical tools alongwith manual chipping and wire brushing to remove loose rust and scale to SSPC SP2 or SP3. Excessive burnishing of steel is to be avoided. Thoroughly dust down all surfaces. The surface should be clean and dry before application of appropriate primer coat and the subsequent coats.

**APPLICATION**

Mix the contents thoroughly before and during use.

Brush: Apply without any thinning.

Roller: Apply with not more than 2% thinning with Thinner No. 800

Conventional Spray: Apply with not more than 2-5% thinning with any standard equipment using a handgun with 66 fluid tip, 70 thou Orifice, 50-60 atomising pressure.

Airless spray: Add upto 5% Thinner 800 if required. Use any standard equipment having pump ratio 30:1. Tip size 0.28.0.38 mm. tip pressure 110-160 kg / cm<sup>2</sup>.

**TYPICAL PAINTING SPECIFICATIONS**

Surface	1st Coat	2nd Coat	3rd Coat	4th Coat
Steel	BP ROZC or Bison HB ZP Primer or Luxol ZC Primer	BP ROZC or Bison HB ZP Primer or Luxol ZC Primer or Bison HB MIO	Torpedo HG Synthetic Enamel	Torpedo HG Synthetic Enamel
Galvanised iron and Aluminium	Degreasing and abrade the surface. Apply Bison Wash Primer followed by any of the above systems excludng the primer coats.			

**Notes :**

1. Do not apply when temperature falls below 10° C or rises above 50° C and when relative humidity rises above 90%. Do not apply during rain, fog or mist.
2. Primed steel work should not be exposed with one coat for a long period. For long term protection, one coat of Bison HB MIO or other top coats may be applied.

**Health & Safety :** Please refer to the separate Safety Data Sheet available with detailed information.

**DISCLAIMER**

The information contained within this Data Sheet is based on information believed to be reliable at the time of its preparation. The Company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

**Data Sheet No. :**  
009/ rev 02  
**Issue Date :**  
July 2003

**BERGER PAINTS INDIA LIMITED** Berger House, 129 Park Street, Kolkata 700017

**Phone :** (033) 2229 9724 (5 lines) / 2249 9754 (4 lines) **Fax :** 91-33-2249 9729 / 2249 9009

**Email :** NORTH : protectondelhi@sify.com SOUTH : bpil\_ch2@sify.com

EAST : bpil\_cl1@vsnl.net WEST : bpilmum\_prot@mtnl.net.in