



Protecteros Exterior Pipe Coating

USES

Specially designed for use on power plants structures and exterior of pipelines.

SCOPE

A highly flexible water-based acrylic latex paint formulated specially for application over Bitumen Coatings and wrappings to protect the undercoat from UV radiation and reduces bleeding

PRODUCT DATA

Type : Single Pack
Composition : Acrylic latex medium suitably pigmented
Application : Brush, roller or spray
Recommended DFT : 20- 30 microns per coat
Theoretical Spreading Rate : 8.3 -12.5 sq. mtr./ltr.

Drying Time :

TOUCH : 45-60 minutes @ 30^oC
HANDLE DRY : 3-4 hrs at 30^oC
HARD DRY : overnight

Overcoating Interval :

MIN : overnight
MAX : one week

Colour : White and Assorted shades

Finish : Smooth and Matt

Packing : 20 Ltrs.

Thinner: Potable water

Storage Life : Upto 12 months as long as the sealed containers are kept under cover in a dry place under normal temperature conditions.

SURFACE PREPARATION

Manual cleaning to St2/ St3 for old and previously coated substrates and spot prime with Protecteros CTE Mastic. The anticorrosive undercoat surface should be perfectly clean, dry prior to the application of coating.

APPLICATION

No dilution is required.

Stir the contents thoroughly and then dilute with potable water if required for workability and maximum up to 5% before application by spray.

Notes:

Do not apply when temperature falls below 10^oC or above 50^oC

Do not apply during rain fog or mist.

Do not apply at relative humidity above 90%.

Health & Safety: Please refer to the separate Safety Data Sheet available with detailed information

DISCLAIMER

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The Company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

Data Sheet No. : 197
Issue Date : July 2008

BERGER PAINTS INDIA LIMITED Berger House, 129 Park Street, Kolkata 700017
Phone : (033) 2229 9724 (5 lines) / 249 9754-58 **Fax :** 91-33-2249 9729 / 2249 9009
Email : NORTH : protectondelhi@sify.com **SOUTH :** bpil_ch2@sify.com
EAST : bpil_cl1@vsnl.net **WEST :** bpilum_prot@mtnl.net.in